


Safe, high-efficiency replacements for fluorescent tubes in:

- Offices
- Showrooms
- Warehouses and storage facilities
- Retail locations
- Schools
- Refrigerated storage areas
- Outdoor/vapor-proof fixtures
- Anywhere T8 fluorescent tubes are used



Features

- Xtreme8 E-ballast design – Type A
- Works with most standard electronic fluorescent ballasts
- Frosted glass tube will not sag or yellow - no pixelation - Excellent heat dissipation
- Exceptional light quality – 300 degree dispersion – Low glare
- Instant on at full brightness – no warm-up time
- Extreme Performance – 50,000+ User Hours
- Earth-friendly design contains no mercury or lead.
- **EcoHX PLUS™**, Cool and Natural color tones



Watts	Length	Product Code	Description	Color Tone	CRI	Lumens	Case Qty.	DLCID
14W	4ft.	LX84EB14EXP	LED/X8/4FT/E-Ballast/14W/EcoHX PLUS	EcoHX PLUS	90+	2400	36	#
14W	4ft.	LX84EB14EXP-G	LED/X8/4FT/E-Ballast/14W/EcoHX PLUS-G*	EcoHX PLUS	90+	2400	36	#
15W	4ft.	LX84EB15C	LED/X8/4FT/E-Ballast/15W/EcoHXC	Cool	85	2200	36	#
15W	4ft.	LX84EB15N	LED/X8/4FT/E-Ballast/15W/EcoHXN	Natural	85	2200	36	#
12W	3ft.	LX83EB12EXP	LED/X8/3FT/E-Ballast/12W/EcoHX PLUS	EcoHX PLUS	90+	1750	36	#
12W	3ft.	LX83EB12C	LED/X8/3FT/E-Ballast/12W/EcoHXC	Cool	85	1600	36	#
12W	3ft.	LX83EB12N	LED/X8/3FT/E-Ballast/12W/EcoHXN	Natural	85	1600	36	#
8W	2ft.	LX82EB8EXP	LED/X8/2FT/E-Ballast/8W/EcoHX PLUS	EcoHX PLUS	90+	1300	36	#
8W	2ft.	LX82EB8C	LED/X8/2FT/E-Ballast/8W/EcoHXC	Cool	85	1200	36	#
8W	2ft.	LX82EB8N	LED/X8/2FT/E-Ballast/8W/EcoHXN	Natural	85	1200	36	#

* **HX-Guard™** coated tubes are NSF certified and USDA approved. **HX-Guard™** coating complies with FDA and OSHA requirements for use in food service and food production facilities.

NOTE: E-Ballast tubes are **NOT** compatible with the BEH432 ballast.
Wattage is determined by ballast factor (Low = 14W – Normal = 19W – High = 23W)

